## CLAIMS

## What is claimed is:

Bol

5

6

7

8

3

ionosyra iidoo

1. A method for servo track writing comprising:

coupling a reference disk and a copy disk to a spindle motor of a servo track writer;

reading the reference disk with a read head of the servo track writer, said reference disk having a plurality of tracks containing servo information; and,

writing said servo information onto a copy disk using a write head of said servo track writer before said copy disk is incorporated into a hard disk drive assembly.

- 2. The method of claim 1 wherein reading the reference disk comprises performing a track following operation, where said track following operation comprises:
- positioning said read head at a first track on said

  reference disk;
- 6 following at least a portion of said first track with
- 7 said read head, said reference disk to be rotated using a
- 8 fluid dynamic bearing spindle;
- 9 determining a position error signal for said read head;
- 10 correcting a position of said read head using said
- 11 position error signal; and,
- reading servo information from at least said portion
- 13 using said read head.

Atty. Docket No.: 155634-0118 Express Mail No.: EL922431925US -19-

Patent Application 427953

HODDEXXE LACE

- 2 said reference disk and said copy disk using a fluid dynamic
- 3 bearing\spindle.
- 1 4. The method of claim 1 wherein writing said servo
- 2 information to the disk comprises writing a plurality of burst
- 3 signals to the disk, said burst signals to be read by a drive
- 4 head of said hard\disk drive assembly to determine a position
- 5 of said drive head.
- 1 5. The method of claim 1 wherein reading the reference
- 2 disk comprises reading the reference disk with a read head of
- 3 the servo track writer where said reference disk is encoded
- 4 with a phase modulated servo pattern.
- 1 6. The method of claim 1 wherein reading the reference
- 2 disk comprises reading the reference disk with a read head of
- 3 the servo track writer where said servo information is
- 4 recorded onto said reference disk using an offline servo track
- 5 writer.

6

- 7. The method of claim 1 further comprising
  2 incorporating said copy disk into a disk stack of said hard
  3 disk drive assembly, copying at least a portion of said servo
  4 information onto a blank disk that is on said disk stack, and
  5 using said servo information to determine a position of a
- 1 8. The method of claim 1 wherein writing said servo 2 information onto said copy disk comprises writing said servo 3 information onto said copy disk where said servo information 4 and said disk copy are to be used in a dedicated servo system.
- 9. A servo track writer comprising:

drive head of said hard disk drive assembly.

- an actuator having a plurality of actuator arms;
- a read head connected to one of said actuator arms;
- a write head connected to another of said actuator arms;
- 5 a chuck to secure a reference disk and a copy disk onto a
- 6 spindle, said spindle to rotate said reference disk and said
- 7 copy disk; and,
- 8 a controller to:
- 9 read the reference disk with said read head, said
- 10 reference disk to include a plurality of tracks containing
- 11 servo information; and,

12	write	said	servo	information	onto	said	сору	disk	using
----	-------	------	-------	-------------	------	------	------	------	-------

- 13 said write head before incorporating said copy disk into a
- 14 hard disk drive assembly.
- 1 10. The servo track writer of claim 9 wherein said
- 2 controller further is to:
- 3 position said read head at a first track on said
- 4 reference disk;
- follow at least a portion of said first track with said
- 6 read head;
- 7 determine a position error signal for said read head;
- 8 correct a position of said read head using said position
- 9 error signal; and
- 11 using said read head.
  - 1 11. The servo track writer of claim 10 further
  - 2 comprising a plurality of copy disks and a plurality of write
  - 3 heads associated therewith.
  - 1 12. The servo track writer of claim 10 wherein said
  - 2 servo information is to be stored in memory before being
  - 3 written to said copy disk.

- 1 13. The servo track writer of claim 9 wherein said 2 spindle comprises a fluid dynamic bearing spindle.
- 1 14. The servo track writer of claim 9, wherein said
- 2 reference disk is encoded with a phase modulated servo
- 3 pattern.
- 1 15. The servo track writer of claim 9, wherein said
- 2 servo information is recorded onto said reference disk using
- 3 an offline servo track writer.
- 1 16. The servo track writer of claim 9 wherein said copy
- 2 disk is to be incorporated into a disk stack of a hard disk
- 3 drive assembly after said servo information has been written
- 4 onto said copy disk, said servo information on said copy disk
- 5 to be used to determine a position of a drive head in said
- 6 hard disk drive assembly where said hard disk drive assembly
- 7 utilizes a dedicated servo system.
- 1 17. The servo track writer of claim, 9, wherein said copy
- 2 disks are to be incorporated into a disk stack of a hard disk
- 3 drive assembly after said servo information has been written

Atty. Docket No.: 155634-0118 Express Mail No.: EL922431925US Patent Application 427953

- 5 to be copied onto a blank disk in said hard disk drive
- 6 assembly\where said hard disk drive assembly utilizes an
- 7 embedded ector servo system.
- 1 18. A servo track writer comprising:
- an actuator having a plurality of actuator arms and heads
- 3 attached thereto
- 4 spindle means to rotate a reference disk and a copy disk,
- 5 said reference disk to contain a plurality of tracks having
- 6 servo information to be read by at least one of said heads;
- means to secure said reference disk and said copy disk to
- 8 said spindle means;
- 9 means to perform a track following operation on said
- 10 reference disk;
- 11 means to write said servo information onto said copy disk
- 12 before said copy disk is incorporated into a hard disk drive
  - 13 assembly.

4

- 1 19. The servo track writer of claim 18 wherein said
- 2 means to perform the track following operation comprises:
- means for positioning a first head on a track on said
- 4 reference disk;
- means for following at least a portion of said track with
- 6 said first head;

- means for determining a position error signal for said
  first head;
  means for correcting a position of said first head using
  said position error signal; and
- means for reading said servo information from at least said portion with said first head.
- 1 20. The servo track writer of claim 18, further
  2 comprising means for incorporating said copy disk into said
  3 hard disk drive assembly, said copy disk to contain said servo
  4 information copied from said reference disk.
- 1 21. A servo track\writer comprising:
- 2 an actuator having a plurality of actuator arms;
- a read head connected to one of said actuator arms;
- a write head connected to another of said actuator arms;
- 5 and,
- 6 a fluid dynamic bearing spindle, said fluid dynamic
- 7 bearing spindle to rotate a reference disk and a copy disk in
- 8 a servo track writing operation.
- a chuck to secure the reference disk and the servo-copy
- 10 disk to said fluid dynamic bearing spindle.
- 11 a controller to:
- perform a track following operation on said reference
- 13 disk, said reference disk to include a plurality of tracks

-25-

- 14 containing servo information to be read by said read head;
- 15 and,
- write said servo information onto said copy disk using
- 17 said write head before incorporating said copy disk into a
- 18 hard disk drive assembly.
- 1 22. The servo track writer of claim 21 wherein said
- 2 track following operation comprises:
- 3 positioning said read head at a first track on said
- 4 reference disk;
- following at least a portion of said first track with
- 6 said read head;

N

H

- determining a position error signal for said read head;
- 8 correcting a position of said read head using said
- 9 position error signal; and
- The reading said servo information from at least said portion
  - 11 using said read head.
    - 1 23. The servo track writer of claim 21 further
    - 2 comprising a plurality of copy disks each having a head
    - 3 associated therewith capable of writing information to said
    - 4 copy disks.

- 1 24. The servo track writer of claim 21 wherein said copy
- 2 disk is to be incorporated into a disk stack of a hard disk
- 3 drive assembly after said servo information has been written
- 4 onto said copy disk, said servo information on said copy disk
- 5 to be used to determine a position of a drive head of said
- 6 hard disk drive assembly where said hard disk drive assembly
- 7 utilizes a dedicated servo system.
- 1 25. The servo track writer of claim 21, wherein said
- 2 copy disks are to be incorporated into a disk stack of a hard
- 3 disk drive assembly after said servo information has been
- 4 written onto said copy disk, said servo information on said
- 5 copy disk to be copied onto a blank disk in said hard disk
- 6 drive assembly where said hard disk drive assembly utilizes an
- 7 embedded sector servo system.
- 1 26. The servo track writer of claim 21, wherein said
- 2 fluid dynamic bearing spindle is an oil bearing spindle.

Atty. Docket No.: 155634-0118 Express Mail No.: EL922431925US Patent Application 427953